

**Distributor:** 



Humidity House | 1140a Axis Cleeve Road | Leatherhead Surrey | KT22 7ND

01372 571200 | humiditysolutions.co.uk info@humiditysolutions.co.uk

## SteamRoom Generators

### **Steam Production**

**Steam Generation for a Steam Room Application** 

A Vapac Steam Generator designed specifically for use with Steam Rooms in the UK.

A full range of 6.68 kW-22.25 kW steam room units are available for optimised performance in the steam room, treatment room, gyms, hotel, leisure and fitness centres as well as domestic environments.

An essential component of an environment that promotes relaxation, health and wellbeing for the mind and body.





# **Steam**Room **Generators**

### **FEATURES**

Temperature	Control on fascia with set-point adjustment and digital display indicating room temperature and set-point temperature	Steam Accessories	Steam hose		
Interlock Connection	230V contact facility to provide interlock for an essence pump	Benefits	Provides stable temperatures Easy to install Low cost maintenance Replaceable cylinders		
Odourless Steam	Odourless steam as standard, alternatively scented can be achieved with the inclusion of scented oils in an essence pump		Hygienic steam system Manufactured in the UK		
LED Status	LED light to indicate unit status				
Low Voltage Control Circuit	24 vac				
Set Up and Go	Once the set point has beer chosen, the operation is fully automatic	1			
Maintenance Friendly	Ease of access to components, including steam cylinder				

STEAM OUTPUT+ELECTRICAL REQUIREMENTS								
Model	Maximum Steam Output Kg/hr	Number of Cylinders +Steam Outlets	Diameter of Steam Outlets mm	Voltage V	Electrical Supply	Maximum Power Rating kW	Full Load Current Range (per cyl) Amps	Maximum Fuse Rating Range Amps
VS9D	9	1	35	230	1 Phase	6.68	30.5	50
VS18D	18	1	35	400	3 Phase	13.35	20.5	32
VS30D	30	1	55	400	3 Phase	22.25	34	50

All 3 phase measured at 400V

## SteamRoom Generators

### **Steam Production**

Steam Generation for a Steam Room Application

DIMENSIONS+WEIGHTS							
Model	VS9D	VS18D	VS30D				
Height* mm	674	674	811				
Width mm	430	430	521				
Depth mm	280	280	376				
Dry Weight Kg	16	39	40				
Wet Weight kg	183	65.5	66.5				







NORTEK GLOBAL HVAC (UK) LTD
Fens Pool Avenue | Brierley Hill
West Midlands | DY5 1QA | UK
+44 (0)1384 489 250
vapacsales@nortek.com | nortek.com

